

# Loose Tubular Terminal Crimping Machine WPM-KAC05B

Model WPM-KAC05B

Stripping length 8-12mm

Speed 1.5s/time

Control method touch screen, electronic control, pneumatic control

Applicable wire BVR hardware: 0.5-4mm<sup>2</sup>,

The soft wire needs to be twisted: 0.5-2.5 mm<sup>2</sup>

Terminal supply vibration plate feeding

Crimping method left and right horizontal crimping in parallel

Rated power supply AC220V 50Hz

Working pressure 0.3-0.8MPA

Working temperature -10/40°C

Weight about 30KG

Dimension 42cmx40cmx39cm



# Automatic wire stripping and crimping machine for tube type terminals



Vibrating plate feeding

Speaker threading port

High-speed steel stripping knife

Touch LCD screen



# Crimping operation is safer



The threading part adopts a trumpet-shaped threading port, fully sealed peeling and crimping, the crimping operation is safer



# Processing sample display

This model is specially designed for single-grain tube terminal crimping.  
Suitable for wire harness processing of 0.5-4mm<sup>2</sup>



# PRODUCT ANALYSIS

Transparent protective cover

Vibrating plate

Unboxing button

Flared threading port

Touch man-machine interface

气压调节阀

接气口

电源接口



# PRODUCT DETAILS



## Flared threading port

The threading part adopts a trumpet-shaped threading port, fully sealed peeling and crimping, the crimping operation is safer

## Vibrating plate feeding

Adopt vibrating plate feeding method, convenient and quick to replace the terminal



## Touch man-machine interface CNC operation

# Internal wiring



# Air pressure regulating valve

Working pressure range: 0.3-0.6mpa



# Power connector



# PRODUCT ACCESSORIES

